



TECHNICAL SPECIFICATIONS

| ATC-250 | |
|----------------------------------|--------------------|
| Operating Voltage | 8 - 16 |
| Test Voltage | 14.4 |
| Input Channels | 1 |
| Output Channels | 1 |
| Continuous Wattage @ 4 Ohm | 100 |
| Continuous Wattage @ 2 Ohm | 225 |
| Continuous Wattage @ 1 Ohm | 325 |
| Max Current Draw (Amps) | 40 |
| Boost Level (dB) | 12 |
| Frequency Response - SUB/FR (Hz) | 30 - 80 / 80 - 20k |
| Low-Pass Filter (Hz) | 80 |
| Remote Subwoofer Control | YES |
| Mounting dimensions (in) | 2.93 x 3.75 x 2 |
| Mounting dimensions (mm) | 74.5 x 95.5 x 52.2 |
| Faceplate dimensions (in) | 3.78 x 4.8 |
| Faceplate dimensions (mm) | 96 x 122 |

DD AUDIO® DIGITAL DESIGNS® Designed in Oklahoma City Made in China CE DDAUDIO.COM

If you have any questions regarding setup, installation or warranty please contact the DD AUDIO® technical support team by email at service@ddaudio.com or by phone at (405) 239-2800.